

# 型號識別


## 型號識別

系列名稱



- P 定值控制型
- AP 帶程序控制型

基本型號



- 910X 160×80mm
- 909X 96×96mm
- 908X 96×48mm
- 907X 72×72mm
- 906X 48×96mm
- 904X 48×48mm

主控制輸出



- 0 無輸出
- 1 繼電器接點輸出
- 2 固態繼電器觸發信號 (SSR)
- 3 4-20mA電流輸出
- 7 正反轉馬達

輔助控制輸出  
(第二組輸出)



- 0 無輸出
- 1 繼電器接點輸出
- 2 固態繼電器觸發信號 (SSR)
- 3 4-20mA電流輸出

警報



- 0 無
- 1 一組警報
- 2 兩組警報

傳送輸出



- 0 無
- 1 PV值4-20mA
- 2 PV值20-4mA
- 3 SV值4-20mA
- 4 SV值20-4mA
- 5 MV值4-20mA
- 6 MV值20-4mA

信號輸入信號



- 1 熱電偶 (T/C)
- 2 熱電阻 (RTD)
- 3 DC4-20mA輸入
- 4 其他線性電流, 電壓輸入

外部設定SV值



- 0 無
- 1 4-20mA外部設定

通訊



- 0 無
- 3 ModBus RTU
- 4 主, 從通訊

防水防塵



- 0 無
- 1 防水
- 2 防塵
- 3 三防
- 4 程序外啟動

輔助電源輸出



- 0 無
- 1 DC24V

供電電源類型



- 0 AC85-265V
- 1 DC24V